

## TECHNICAL DATA SHEET

### PANELTIM® MULTIPOWER

### PP COPO

**Material:** PP Copo Prime (Polypropylene Copolymer)

**Depth:** 50 mm

**Surface:** Both sides smooth

**Internal Cell Structure:** 50 mm x 50 mm

**Size:** 1200 mm x 1000 mm  
2600 mm x 1000 mm



1200 mm x 1000 mm



2600 mm x 1000 mm

**Exterior Wall Thickness:**

| Size              | Wall Thickness |
|-------------------|----------------|
| 1200 mm x 1000 mm | 3.3 mm         |
| 2600 mm x 1000 mm | 4.3 mm         |

**Weight:**

| Size              | Weight                 |
|-------------------|------------------------|
| 1200 mm x 1000 mm | 11.5 kg/m <sup>2</sup> |
| 2600 mm x 1000 mm | 12.8 kg/m <sup>2</sup> |

**Fire Class:** Class E (ISO 11925-2 assessment without test certificate)

**UV Resistance:** (ASTM D 4329)

**(Köppen-Geiger) Climate Classification:**

|      |  |
|------|--|
| UVR: | Cfa, Cfb/Cfc, Dfa/Dwa, D, E, H   |
| UVW: | Af, Aw, Am, BW, BW <sub>h</sub> , BW <sub>k</sub> , BSh, Cwa, Cwb, Cwc, Csa, Csb |

UV resistance is not related to panel surface expansion

**Food Contact:** Certificates available upon request

**Recycling:** 100% recyclable  
Recycling Code:



**Disclaimer:**

This information contains only typical properties of the products. This means these values can deviate. It is the customer's responsibility to inspect and test the product(s) in order to establish the suitability of the product(s) for its and its customers particular purposes. The customer is responsible for the appropriate, safe and legal use while processing and handling all product(s) purchased from us. Nothing herein is intended to be nor shall it constitute a warranty whatsoever, in particular, warranty of merchantability or suitability for a particular purpose.

The latest version of this technical data sheet will be available on our online platform. Contact Paneltim for more information.